




SPECIFICATIONS

60 Ton Trailer

ETNYRE BLACKHAWK CLASSIC SERIES RTN60TD3-R4A (6000P SERIES)



- General:** 60 ton capacity, three axle, non-ground engaging hydraulic removable gooseneck, lowbed trailer for hauling various construction equipment not to exceed 120,000# in any 12' of deck in 3+1 (14'-1" spread) axle configuration.
- Gooseneck Type:** Hydraulic removable, non-ground engaging, pin and stirrup connection, high lift scraper neck design w/aluminum top cover plate
- Gooseneck Travel:** 42" gooseneck travel, (26" up; 16" down) with built in adjustable travel height feature for fifth wheel or road clearance adjustment (2" up or 6" down).
- Gooseneck Support Cylinder:** One (1) 3-1/2" diameter, 12" stroke adjustable hydraulic support cylinder to support gooseneck when detaching to eliminate blocking; with control on drivers side
- Fifth Wheel Height:** 50" Loaded; adjustable 48", 50", 52", 54", 56" without shim blocks
- Swing Clearance:** 108" Radius maximum (16" King Pin setting)
- Hydraulic Power:** From tractor wet kit (P.T.O.). Maximum operating pressure 2500 p.s.i. Optional: Plumbed for dual system including tractor wet kit/P.T.O. and power package operation.
- Hydraulic Lift Cylinders:** Two (2) 8" diameter, 20" stroke double acting hydraulic cylinders mounted horizontally in gooseneck upper frame work with control on drivers side.
- Kingpin:** Standard 2" SAE approved mounted in 5/16" 5th wheel plate.
- Gooseneck to Deck Connection:** (2) Vertical teardrop castings on gooseneck to accept (2) 3-1/2" diameter horizontal pins at front of deck. Cross shaft is 3" dia. stressproof (100,000 min. yield). Deck has alignment guide for gooseneck self-alignment to deck. Air actuated vertical lock pin gooseneck to deck with manual safety lock.
- Platform Length:** 26' (Clear, unobstructed)

Platform Width:	8'-6" (102")
Deck Construction:	(4) 16" deep/full length one piece (no splices) I-Beams; 100,000 p.s.i. flanges (fully cambered beams). Tapered top and bottom first 9'.
Crossmembers:	One (1) piece junior I-beams M12" X 11.8# pierced through mainbeams on 20" centers.
Outriggers:	12" heavy duty cast steel, swinging and removable type w/double hook-on removable in the first position.
Deck Height:	22" Loaded; adjustable 16", 18", 20", 22", 24". (@front of deck)with 50" loaded 5 th wheel height.
Road Clearance:	6" Loaded; adjustable 0", 2", 4", 6", 8". (at front of deck) with 50" loaded 5 th wheel height.
Lash Rings:	Twelve (12) 1" forged D-rings, bent style 6 each side of deck.
Lashing Slots:	Four (4) - One (1) on bottom side outside edge of bolsters.
Flagholder Slots:	Six (6) - One (1) on each end of bolsters and half bolsters.
Decking:	2" apitong, outside of mainbeams attached by self tapping screws.
Ramps:	31" Front folding ramps steel, double hinged, w/traction bars.
Rear Loading Features:	41° sloped ramp ahead of tires, wide center full load bearing, drop bolsters between axles, rear load bearing 1/2 drop bolster after 3 rd axle.
Suspension:	Ridewell air ride suspension with manual +3"/-3" height adjustment in 1-1/2" increments, and manual exhaust valve.
Axles:	Three (3) 25,000# capacity (full width) with 3/4" wall on 55" axle centers. Override chains on all axles.
Wheels:	Steel disc, hub piloted type, painted white, outboard mount with oil seals.
Tires:	(12)-275/70R 22.5 (H) 16 P.R. Radials.
Brakes:	16-1/2" x 7" air with automatic slack adjusters, spring brake chambers on center axle. Brakes to be rated at a minimum of 23,000# per axle.
Anti-Lock Brakes:	None (Trailer exceeds 120,000 # GVWR).
Boomwell:	Recessed boomwell w/xtra low 1 st crossmember (open) over axles #1, #2, & #3 and rear half bolster.
Lights and Wiring:	Truck-Lite® L.E.D. sealed system.
Paint:	Shot blast, clean, prime, paint with (2-part urethane) black, red, or yellow finish.
Bucket Trough:	Last 3 crossmembers in deck covered with 1/4" steel plate.
Frame Reinforcement:	For 3+1 (14'-1" spread) 4th axle.
Top Flange Reinforcement:	Top flange outside main beams.
Mudflaps:	Rubber type rear of axle #3
4TH AXLE:	Flip/removable (included but can be purchased separately),