



- 1) Check the box on the left by the option you would like.
- 2) If line item is grayed out, it is not available with the option you picked.
- 3) Fill in the red text if applicable.

Livebottoms	
Length	
	31' (LB-231)
	32' (LB-232)
	33' (LB-233)
	34' (LB-234)
	35' (LB-235)
	36' (LB-236)
	37' (LB-237)
	38' (LB-238)
	39' (LB-239)
	40' (LB-240)
	41' (LB-241)
CAPACITY WITHOUT BIN EXTENSIONS	
	22.5 CY
	23.5 CY
	24.0 CY
	25.0 CY
	25.5 CY
	26.5 CY
	27.5 CY
	28.0 CY
	29.0 CY
	30.0 CY
	30.5 CY
CAPACITY WITH BIN EXTENSIONS	
	Bin Extension
	31.0 CY
	32.0 CY
	33.0 CY
	34.0 CY
	35.0 CY
	37.0 CY
	38.5 CY
	39.5 CY
	41.0 CY
	42.0 CY

43.5 CY
Livebottom Undercarriage
Aluminum hubs (in lieu of steel hubs) - per axle
Dura-Lite hubs - per axle
HP Bearing (same size inner and outer) - per axle
Centrifuse Drums - per axle
Axles and Brakes
23,000# brake rating - per axle
25,000# brake rating - per axle
Knorr Disc Brakes - per axle
Meritor Disc Brakes - per axle
Air add-on axle - no lift - 23,000#
23,000# air add-on axle, steerable & liftable (w/ manual controls)
23,000# additional axle, air ride & lift (w/dual tires)
13,000# additional axle, air ride & lift (w/single tires)
Air add-on axle, steerable & liftable (RM60 Controls)
Auto lift axle
25,000# air ride axle (w/ manual exhaust valve)
5" round 25,000# rated air ride axle
Hubometer
P.S.I. Automatic Tire Inflation System
Anti-lock brakes (4S/2M sytem)
Anti-lock brakes (6S/3M sytem)
Suspension
Hendrickson Turner Intraxx Suspension
Bogies
Aluminum Bogie - Tandem
Aluminum Bogie - Tridem
Tires and Wheels
11R22.5 (G) Tires
11R24.5 (G) Tires
295/75R22.5 (G) Tires
285/75R24.5 (G) Tires
385/R22.5 (J) Super Single Tires
445/50R22.5 (L) Michelin X One XTE, 14" X 22.5" aluminum wheels, machine finish, w/ TP-type axles, 92" out to out, per axle
455/55R22.5 (L) Michelin X One XTE, 14" X 22.5" aluminum wheels, machine finish, w/ TP-type axles, 92" out to out, per axle
Alcoa aluminum wheels, outside polished, inside machine finished, outboard mount, hub piloted - per axle
Accuride aluminum wheels, outside extra polished, inside standard polish, outboard mount, hub piloted - per axle
Wheels, outside Alcoa aluminum polished, inside steel disc, outboard mount, hub piloted - per axle
Wheels, outside Accuride extra polished, inside steel disc, outboard mount, hub piloted - per axle

	Alcoa aluminum wheels, outside Dura-Brite, inside machine finish, outboard mount, hub piloted - per axle
	Accuride aluminum wheels, outside Accushield, inside standard polish, outboard mount, hub piloted - per axle
	Wheels, outside Alcoa aluminum Dura-Brite, inside steel disc, outboard mount, hub piloted - per axle
	Wheels, outside Accuride aluminum Accushield, inside steel disc, outboard mount, hub piloted - per axle
Optional Equipment	
	Front Fenders, aluminum diamond plate
	Flow valve at rear
	Backup alarm
	Non-metallic paint (other than standard colors) color match PAINT COLOR..... PAINT CODE.....
	Electric front-to-rear tarp
	Remove insulation - per foot
	Bi-fold doors
	High-lift Door
	Plastic fenders - per tandem
	Dual belt drive - 12.2" cubic inch displacement hydraulic motor
	Reversing belt feature w/ control valve
	10 Gal. aluminum tank w/ 25' hose reel and spray wand, mounted below driver's side mirror, pressurized air system
	15 Gal. plastic tank w/ 25' hose reel and spray wand, mounted below driver's side mirror, 12v electric pump