Specification Sheet

Quote: 0051523-01

Quoted: 9/22/2025

Custom Built For:

Series: **SLIDING AXLE**

Model: **55TL3-SA**

Item	Description
CAPACITY	55 TONS DISTRIBUTED (35 TONS IN ANY 10')
PLATFORM WIDTH	8'-6"
PLATFORM LENGTH	53'-0"
PLATFORM HEIGTH	37"
CROSSMEMBERS SPACING	ON 8" CENTERS
AUXILIARY CROSSMEMBERS	OUTSIDE MAINBEAMS BETWEEN CROSSMEMBERS
GOOSENECK TYPE	FIXED FULL WIDTH, VERTICAL DROP
FIFTH WHEEL HEIGHT	48" LOADED
SWING CLEARANCE	84"
TOOLBOX	IN FRONT CORNER OF GOOSENECK - CURB SIDE
TOOLBOX	IN FRONT CORNER OF GOOSENECK - DRIVER SIDE
SPARE TIRE AND WHEEL	245/75R17.5 (H) AND ALCOA ALUMINUM WHEELS: POLISHED OUTERS, MACHINE FINISH INNERS, 6.75” X 17.5
SPARE TIRE CARRIER	MOUNTED FRONT OF TRAILER
25HP GAS POWER PACK	ON TOP OF GOOSENECK
HEADACHE RACK	BOLT-ON
AIR BRAKES	12.25” X 7 ½” AIR W/ AUTO SLACKS ADJUSTERS
ANTI-LOCK BRAKES	6S/3M SYSTEM (6-SENSORS/3-MODULATORS)
SPRING BRAKES	ON 2ND AXLE
AXLES	(3) 25,000# NOMINAL
TIRES	(12) 245/70R17.5 (H)
ALCOA ALUMINUM WHEELS	POLISHED OUTERS, MACHINE FINISH INNERS, 6.75” X 17.5”
SUSPENSION	AIR RIDE WITH 60" SPACING
MANUAL EXHAUST VALVE	ON ALL AXLES
LIQUID FILLED AIR GAUGE	W/ CHART
LIGHTS	L.E.D. RUBBER SEALED SYSTEM
AMBER L.E.D. STROBES	IN 3RD TAIL LIGHT POSITION
L.E.D. WORK LIGHTS	
LASH RINGS	(12) TOTAL-6 PER SIDE OF DECK
DECKING	1 1/2" APITONG, FULL WIDTH (6-7 DEGREE LOAD ANGLE, 15 DEGREE DUMP ANGLE)
RUBBER ENCASED STEEL	ON APPROACH RAMP
BOLT-ON FOLD OUT STEP	ON LOWER DECK
CHAIN SLOTS	OUTER BEAMS ON 24" CENTERS
CHAIN SLOTS	INNER BEAMS ON 24" CENTERS
CHAIN SLOTS	REAR TAIL
PAINT	GLOSS BLACK
LANDING GEAR	2-SPEED
20,000# HYDRAULIC WINCH	INCLUDES 100' OF 9/16" CABLE AND HOOK (BLUETOOTH)
WINCH GUARD	
BLUETOOTH REMOTE	FULL TRAILER

Specification Sheet

Quote: 0051523-01

Quoted: 9/22/2025

OVERSIZE LOAD BANNER	REMOVABLE
FLAG HOLDER WITH THUMBS SCREWS	(1) AT FRONT AND (1) AT REAR

Etnyre reserves the right to modify pricing on all quotes and orders with material and labor surcharges as needed